

**COMPLETE LISTING OF CLAIMS**  
**IN ASCENDING ORDER WITH STATUS INDICATOR**

Claim 1 (currently amended): An electric keyboard assembly comprising:  
a plurality of keys that are each pivotally moved by a key depressing operation; and  
a plurality of seesaw-type mass members that each have first and second arms extending substantially horizontally in opposite directions from a pivotal center of the mass member, and a follower arranged on said first arm, said mass members being disposed in a manner associated with said plurality of keys, respectively, and each pivotally moved about said pivotal center by a driving force generated by depression of a corresponding one of said plurality of keys and received via said follower, said first arm of said mass member popping up to a level higher than said corresponding key when said corresponding key is depressed; and  
a plurality of distinct weight members that are carried separately by said first arm and said second arm, respectively, and  
wherein a distance between said pivotal center and said weight member disposed in said first arm is set to a smaller value than a distance between said pivotal center and said weight member disposed in said second arm.

Claim 2 (previously presented): An electric keyboard assembly comprising:  
a plurality of white keys that are each pivotally moved by a key depressing operation;  
a plurality of black keys that are each pivotally moved by a key depressing operation;  
a plurality of seesaw-type mass members that each have a first arm and a second arm  
each extending from a pivotal center of the mass member, said plurality of mass members being  
disposed in a manner associated with said plurality of white keys and black keys, respectively,  
and being each pivotally moved about said pivotal center when a corresponding one of said  
plurality of white keys or black keys is depressed, said plurality of mass members each having a  
resin portion, said resin portion of one of said mass members associated with one of said white  
keys being substantially identical in configuration with said resin portion of another of said  
mass members associated with one of said black keys which is adjacent to said one of said white  
keys; and  
a plurality of insert weight members that are carried respectively by said first and second  
arms of each of said mass members, and  
wherein said insert weight members have respective weights thereof set separately from  
each other, such that key-touch responses of said one of said white keys and said one of said  
black keys adjacent thereto are made similar to each other.

Claim 3 (original): An electric keyboard assembly comprising:  
a plurality of keys that are each pivotally moved by a key depressing operation;  
a plurality of mass members that each have a body, and are disposed in a manner  
associated with said plurality of keys, respectively, said plurality of mass members being each  
pivotally moved about a pivotal center thereof when a corresponding one of said plurality of  
keys is depressed, said body of each of said plurality of mass members being formed of resin and  
having at least one hollow weight-mounting portion formed therein; and  
at least one weight member that is mounted in said at least one hollow weight-mounting  
portion, said at least one weight member each having a hollow portion formed therein, and  
wherein said hollow portion of said at least one weight member of each of said plurality  
of mass members having a volumetric capacity thereof set separately from each other so as to  
accomplish key scaling to key-touch response.

Claim 4 (previously presented): An electric keyboard assembly comprising:  
a plurality of keys that are each pivotally moved by a key depressing operation;  
a plurality of seesaw-type mass members that each have a body, and first and second arms extending in opposite directions from a pivotal center thereof, said plurality of mass members being disposed in a manner associated with said plurality of keys, respectively, said plurality of mass members being each pivotally moved about said pivotal center when a corresponding one of said plurality of keys is depressed, said body of each of said plurality of mass members being formed of resin, said body including a follower for receiving a driving force generated by said key depressing operation, a stopper abutment portion for abutment with a stopper for setting a pivotal movement-completing position of said mass member, and a sensor depressing portion for depressing a sensor for detecting said key depressing operation, each of said plurality of mass members having first and second weight-mounting portions formed in said first and second arms, respectively; and  
first and second insert weight members that are carried by said first and second weight-mounting portions, respectively, and  
wherein said follower, said stopper abutment portion, and said sensor depressing portion each have an identical configuration between ones of said plurality of mass members for a plurality of octave sections, to thereby provide ease of operation of mounting said first and second insert weight members in a corresponding one of said plurality of mass members; and  
wherein a plurality of combinations of weights of said first and second insert weight members to be mounted in said first and second arms, respectively, are set between said ones of said plurality of mass members for said plurality of octave sections, while said mass members of each of the octave sections are identical in configuration with each other.

Claim 5 (original): An electric keyboard assembly according to claim 4, wherein said first and second insert weight members each have an outer periphery and are formed of a sheet member, said outer periphery being configured such that it can be fitted in a corresponding one of said first and second weight-mounting portions of each of said plurality of mass members, and wherein said plurality of combinations of weights of said first and second insert weight members to be mounted in said first and second arms, respectively, can be set by at least one of changing weights of said first and second insert weight members and changing thickness of said first and second insert weight members, while maintaining said outer periphery identical in configuration between said first and second insert weight members.

Claim 6 (original): A keyboard assembly comprising:

- a plurality of pivotally movable members that each have a pivotally movable member body and are each pivotally moved by a key depressing operation; and

- a plurality of weight members each having an outer periphery and mounted in said plurality of pivotally movable members;

- wherein said weight members mounted in said plurality of pivotally movable members are different in weight from each other so as to vary key-touch response between said keys or between groups of said keys during key depression, thereby accomplishing key scaling to key-touch response;

- at least one of said weight members being formed of a plurality of weight component parts laminated one upon another and fixed together;

- said plurality of weight component parts having a substantially identical outer shape in plan view;

- said pivotally movable members being formed by outsert molding;

- said outer periphery of each of said weight members being covered by resin outserted thereon;

- said pivotally movable member body comprising an outserted portion covering said outer periphery of each of said weight members;

- said weight members mounted in said pivotally movable members being different in weight between said keys or between key ranges.

Claim 7 (original): A method of manufacturing a weight member mounted in a pivotally movable member provided in a keyboard assembly, said weight member comprising a plurality of weight component parts laminated one upon another, the method comprising the steps of:

intermittently moving a sheet member formed of a metal, and forming half-punched portions each having a projection on one side surface of said sheet member and a recess on an opposite side surface thereof, during stoppage of intermittent movement of said sheet member;

punching, using a cavity blade, a portion of said sheet member along an outer periphery thereof which is located radially outward of said half-punched portions to form each of said weight component parts having said half-punched portions, and sequentially laminating the formed weight component parts one upon another within said cavity blade such that the recesses or projections of the half-punched portions of an leading one of the weight component parts are fitted with the projections or recesses of the half-punched portions of a following one of the weight component parts; and

removing said weight member formed of a predetermined number of said weight component parts laminated one upon another from said cavity blade when said predetermined number of said weight component parts are laminated one upon another.

Claim 8 (original): A method according to claim 7, wherein said plurality of weight component parts have a substantially identical outer shape in plan view.